


N Leadville Ave

Sun Valley Rd

Sun Valley Rd

N Leadville



SPEED LIMIT	TAPER LENGTH (L) FEET
40 MPH OR LESS	$L = WS^2/60$
45 MPH OR MORE	$L = WS$

L=taper length in feet
 W=width of offset in feet
 S=sposted speed limit, or in off-peak 85th-percentile speed prior to work starting, or the anticipated operating speed in mph

ROAD TYPE	DISTANCE BETWEEN SIGNS		
	A	B	C
URBAN (LOW SPEED) <35	100 FT	100 FT	100 FT
URBAN (HIGH SPEED) >35	350 FT	350 FT	350 FT
RURAL	500 FT	500 FT	500 FT
EXPRESSWAY/FREEWAY	1000 FT	1500 FT	2640 FT

Author: Chad Robinson

CERT:799441

Comments:

- *All equipment shall be MUTCD compliant
- *All traffic control shall be managed by a ATSSA certified supervisor
- *All work will be performed during daylight hours
- *A minimum of 12' lane widths shall be maintained



ADA IMPROV. EAST AVE. D



Legend

- North Indicator
- ADA Ramp
- Sign Stand
- Tubular
- Work Area
- Pedestrian wall

Author: Chad Robinson CERT:799441

Comments:

- *All equipment shall be MUTCD compliant
- *All traffic control shall be managed by a ATSSA certified supervisor
- *All work will be performed during daylight hours
- *A minimum of 12' lane widths shall be maintained

SPEED LIMIT	TAPER LENGTH (L) FEET
40 MPH OR LESS	$L = WS / 50$
45 MPH OR MORE	$L = WS$

L=taper length in feet
W=width of offset in feet
S=posted speed limit, or in off peak 85th percentile speed prior to work starting, or the anticipated operating speed in mph

ROAD TYPE	DISTANCE BETWEEN SIGNS		
	A	B	C
URBAN (LOW SPEED) <35	100 FT	100 FT	100 FT
URBAN (HIGH SPEED) >35	350 FT	350 FT	350 FT
RURAL	500 FT	500 FT	500 FT
EXPRESSWAY/FREEWAY	1000 FT	1500 FT	2640 FT



